

Winpak W101 Rotary Filling and Sealing Machine – Features and Specifications

- Product Applications: Condiments, Dips, Sauces, Salad Dressings, Cream Cheese, Sour Cream, Syrups, Ketchup and many other liquid and semi-viscous products
- Cup Rim Diameters: 51mm, 60mm, 75mm (one size with machine, additional sizes require extra tooling not included in base)
- Cup Materials: Polypropylene, Polypropylene Barrier, Polystyrene and Polystyrene Barrier
- Package Format: Round, Pre-formed Cups
- Lid Format; Individually Die-cut Foil or Plastic Lids
- Lid Diameters: various based on cup size(s) selected
51mm Montreal, 52mm Peoria, 61mm Montreal, 62mm Peoria, 75.5mm and 79mm (usually for juice to cover the drinking lip)
- Product Filling Range – Minimum 0.375 fl. oz. (11ml) to Maximum 6.0 fl. oz. (177ml)
- Filling Temperature Range: Minimum 34°F (1°C), Maximum 175°F (80°C) hot fill parts required
- Packages per Cycle – One
- Cycles per Minute – Up to 40 (40 cups per minute)
- Small 32" X 41" X 72" Footprint
- Camco Precision Drive (table index)
- Automatic Lid Pick & Place
- Single cartridge heater head 220V
- Completed container, Automatic Removal
- 6 Station, 6 cup Dial plate & Tooling with quick change diameter parts available
- Allen Bradley Logic Controller
- Safety Sensors: If no cup, no fill; If no fill, no foil placement
- NEMA 4x Control Panel
- HMI mounted at eye level on pack off side





1111 Winpak Way
Sauk Village, IL 60411

Tel: (708) 753-5700
Fax: (708) 757-2447
Email: wppinfo@winpak.com

- Perimeter Guarding with Interlocks
- Electrical: 220-240V - 1Ph - 20A Electrical Power Supply
- Air: 80psi Dry, oil-free, clean air supply